

Please fill out **BOTH** sides of this form. This form is for **BOTH** racedays.



SERIAL NUMBER FORM

CLASS _____ KART # _____

DRIVER'S NAME _____ SIGNATURE _____

ENGINE SERIAL# _____ CHASSIS SEAL# _____

DRY MG TIRE SERIAL #'S

(5-8 for IAME Jr, IAME Sr, Shifter, and Shifter Master, ONLY)

Saturday

Sunday

1. _____

5. _____

2. _____

6. _____

3. _____

7. _____

4. _____

8. _____

WET MG TIRE POLICY

202.2 Rain Tires:

MG SW tires shall be used. Tire treatments of any kind and/or tire warmers are illegal.

*No limit on the number of rain tires

Micro / Mini: MG SW **4.2/4.2** Tire Set

Jr / Sr / Master: MG SW **4.2/6.0** Tire Set

INSTRUCTIONS:

1. PLEASE TURN THIS FORM IN TO THE GRID OFFICIAL JUST PRIOR TO GOING ON TRACK FOR PRACTICE ON **SATURDAY**
2. ENGINE SERIAL #, CHASSIS SEAL, AND DRY TIRE SERIAL NUMBERS ARE MANDATORY. (all tires must have readable bar codes to be legal)

I present this kart for competition and hereby certify that all items on this form have been inspected and filled out properly, and that these tires will be the only ones used during their set times.

X _____

**Pre-Tech Opens at 7:00 A.M.
This form must be turned in to Pre-Tech BEFORE Saturday Warmup.**

Please fill out **BOTH** sides of this form. This form is for **BOTH** racedays.



Pre-Tech Inspection Check Sheet

Race Class: _____

Date: ___/___/___

Driver Name: _____

Kart Number: _____

Steering Group - The following shall be safety wired, safety clipped, or cotter pinned	Initial
Steering Wheel Hub Bolts (all)	
Bolt - Steering hub to steering shaft	
Bolt - Steering shaft to chassis	
All Bolts - Tie rods at steering shaft and spindles	
Kingpin Bolts	

Braking Group - The following shall be safety wired, safety clipped, or cotter pinned. Any lock nuts must be all metal type	Initial
Clevis Pin or Bolt - Brake pedal to frame	
Clevis Pin or Bolt - Brake rod or cable, pedal AND master cylinder end	
Bolts - Master cylinder(s) to chassis	
Bolts - Brake caliper(s) to chassis bracket AND any brackets to frame	
Brake Test - Reasonable force on brake pedal locks applicable wheels	

Other Items	Initial
Weight Mounting Bolts - Painted white AND must be double nutted or drilled with safety wire, cotter pin, or safety clip.	
Clevis Pin or Bolt - Throttle pedal to chassis SHOULD be safety wired, safety clipped, or cotter pinned.	
Throttle System - Throttle return system of some sort MUST be functional.	
Kart Numbers - High contrast minimum of 4" tall visible on 4 sides of kart	
Seat Mounting - Seat mounted via industry standard methods - nylock nuts suggested	
CIK Bodywork - Securely mounted via industry standard hardware	
Transponder Mounting - Transponder mounted on the back of the seat	
Driver Protective Clothing - Helmet (Per WKA Guidelines), gloves, suit/jacket, footwear, neck protection	
Micro, Mini, and Junior classes - SFI approved chest protection MANDATORY	

Signature

_____/_____/_____
Date

I present this kart for competition and hereby certify that all items on this form have been inspected and corrected as necessary, and will be maintained in accordance with this document and all applicable USPKS rules for the remainder of this event.

It is driver & mechanic's sole responsibility to ensure kart remains in safe working order throughout event. All nuts, bolts, etc., shall be maintained to manufacturer's specifications. Kart racing is a dangerous sport and can lead to serious injury or death. Signature on this document accepts all risk and liability for specified kart during competition day.